





-  2x2' ACOUSTICAL LAY-IN CEILING GRID AND TILE
-  TBTP GYPSUM CEILING
-  2'x2' CERAMIC TILE
-  2'x2' SECURITY STEEL LAY-IN PANELS HEAVY DUTY GRID SYSTEM W/ ACOUSTICAL BATT SCREWED ACCESS PANEL- SEE DETAILS
-  STEEL PLATE CEILING

EXPOSED PAINTED CEILING WHERE NOTED

NOTE:  
 1. INSTALL STEEL BRACKET IN CMU COURSE @ 8'-0" FOR STEEL PLATE CEILING. COORDINATE ALL SPRINKLER/MEP REQ. OPENINGS PRIOR TO INSTALLATION FOR STEEL CEILING.  
 2. ALL ACCESS PANEL LOCATIONS NEED TO BE COORDINATED WITH ARCHITECT.

1 1ST FLOOR REFLECTED CEILING PLAN - AREA A  
 SCALE: 1/8" = 1'-0"

REV. #	DESCRIPTION	DATE
1	CONSTRUCTION	12/07/10
2		
3		
4		
5		

PROJECT NUMBER: 0905  
 DATE: 10/12/2010  
 SHEET TITLE: 1ST FLOOR REFLECTED CLG. PLAN PART A  
 SHEET NUMBER: A3.01A